

RFQ NUMBER : 2012201698

DATE : 30.03.2022

REQ No : 1012201420

REQ TITLE: BATTERY 1012201420

DELIVERY LOCATION : 0051 - CENTR STROE(TRN)

CLOSING DATE : 07.04.2022

CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
1	2700121064		BATTERY CELL; NICKEL CADMIUM; MAKE ALCAD; TYPE: LC70P; CAPACITY: 70 AH; DIMENSION: H358 X W192 X L68 (MM)THE BATTERY CELLS ARE TO BE SUPPLIED DRY AND THE ELECTROLYTE TO BE SUPPLIED IN CONTAINERS STACKED IN 2 LAYERS WITH A SIZE 25 LITERS EACH.	2	EA				
2	2700094525		BATTERY_DRY CELL, RECHARGEABLE; TYPE: NICD; VOLTAGE: 1.45 TO 1.7VDC (HIGH LEVEL); AMP HOURS: 110AH; CONNECTION: M10 BOLT-ON TERMINAL; STANDARD: IEC 62485-2, IEC 60623; MFR: SAFT: MPN: SBLE 110-2: MFR: SAFT: MPN: KL110P: ADDITIONAL INFO: BRAND: NIFE; REGION: SWEDE N; APPLICATION: DFO 110VDC SYSTEM; CODE: 0904	2	EA				
3	2700096558		BATTERY_DRY CELL, RECHARGEABLE; TYPE: NICD; AMP HOURS: 60AH; SIZE: 4.8IN WD, 1.85IN LG, 12.2IN HT; STANDARD: IEC 60623; MFR: HOPPECK E BATTERIEN GMBH & CO KG: MPN: FNC203L: ADDITIONAL INFO: REGION: GERMANY; TEMPERATURE RATING: -40 TO 60DEG C		EA				
4	2700000674		BATTERY_DRY CELL, RECHARGEABLE; TYPE: NICD; AMP HOURS: 266AH; SIZE: 7.64IN WD, 4.53IN LG,	1	EA				



RFQ NUMBER : 2012201698

DATE : 30.03.2022

REQ No : 1012201420

REQ TITLE : BATTERY 1012201420

DELIVERY LOCATION : 0051 - CENTR STROE(TRN)

CLOSING DATE : 07.04.2022

CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			12.2IN HT; STANDARD: IEC 60623; MFR: HOPPE CKE BATTERIEN GMBH & CO KG: MPN: FNC308M: ADDITIONAL INFO: TEMPERATURE RATING: -40 TO 60DEG C; APPLICATION: STATION BATTERY CHARGER AND DISTRIBUTION BOARD; 110V						
5	2700121068		BATTERY CELL; NICKEL CADMIUM; MAKE SAFT; TYPE: SBH265-1; CAPACITY: 265 AH; DIMENSION: H354 X W195 X L232 (MM)	2	EA				
6	2700069348		BATTERY_DRY CELL, RECHARGEABLE; TYPE: NICD; VOLTAGE: 1.43 TO 1.5VDC; AMP HOURS: 1720AH; CONNECTION: 4 X M10 BOLT/POLE; STANDARD: IEC 62485-2, IEC 60623; MFR: SAFT: MPN: SBL 860-1		EA				
7	2700096554		BATTERY_DRY CELL, RECHARGEABLE; TYPE: NICD; VOLTAGE: 1.42VDC (FLOATING LEVEL), 1.45 TO 1.7VDC (HIGH LEVEL); AMP HOURS: 90AH; CONNECT ION: M8 BOLT-ON TERMINAL; STANDARD: IEC 62485-2, IEC 60623; MFR: SAFT: MPN: SBL 90: ADDITIONAL INFO: BRAND: NIFE; REGION: SWEDEN		EA				
8	2700125381		BATTERY CELL; NICKEL CADMIUM; MAKE SAFT; TYPE: SBLE375-2; CAPACITY: 375 AH; DIMENSION:	2	EA				



RFQ NUMBER : 2012201698

DATE : 30.03.2022

REQ No : 1012201420

REQ TITLE : BATTERY 1012201420

DELIVERY LOCATION : 0051 - CENTR STROE(TRN)

CLOSING DATE : 07.04.2022

CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			L=252(MM), W=195(MM), H=405(MM)						
9	2700121071		BATTERY CELL; NICKEL CADMIUM; MAKE SAFT; TYPE: SBM830-1; CAPACITY: 830 AH; DIMENSION: H410 X W195 X L353 (MM)	2	EA				
10	2700096556		BATTERY_DRY CELL, RECHARGEABLE; TYPE: NICD; AMP HOURS: 95AH; MFR: SAFT: MPN: SLM 95: ADDITIONAL INFO: BRAND: NIFE; REGION: SWEDEN		EA				
11	2700121061		BATTERY CELL; NICKEL CADMIUM; MAKE SAFT; TYPE: SBL500-1; CAPACITY: 500 AH; DIMENSION: H406 X W195 X L171 (MM)	1	EA				
12	2700094526		BATTERY_DRY CELL, RECHARGEABLE; TYPE: NICD; VOLTAGE: 1.4VDC (FLOATING LEVEL), 1.45 TO 1.7VDC (HIGH LEVEL); AMP HOURS: 161AH; SIZE: 1 95MM WD, 127MM LG, 406MM HT; CONNECTION: M10 BOLT-ON TERMINAL; STANDARD: IEC 60623; MFR: SAFT: MPN: SBM 161-2: MFR: SAFT: MPN: KM11 6 P: ADDITIONAL INFO: BRAND: NIFE; REGION: SWEDEN; APPLICATION: DFO 380 UPS SYSTEM; CODE: 0811		EA				
13	2700121065		BATTERY CELL; NICKEL CADMIUM; MAKE SAFT; TYPE: SBM277-3; CAPACITY: 277 AH; DIMENSION: H406 X W195 X L337 (MM)	2	EA				





RFQ NUMBER : 2012201698

DATE : 30.03.2022

REQ No : 1012201420

REQ TITLE: BATTERY 1012201420

DELIVERY LOCATION : 0051 - CENTR STROE(TRN)

CLOSING DATE : 07.04.2022

CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
14	2700124947		ELECTROLYTE FOR BATTERIES; TYPE-E22	300	L				
			(POTASSIUM HYDROXIDE (KOH)+LITHIUM						
			HYDROXIDE (LIOH) SOLUTION); SUITABLE FOR						
			NICKLE CADMIUM (NI-C						
			D) BATTERIES						

TOTAL AMOUNT IN WORDS: TOTAL AMOUNT:

SPECIAL NOTES / INSTRUCTIONS:

The battery cells are to be supplied dry and the electrolyte to be supplied in containers stacked in 2 layers with a size 25 Liters each.

STANDARD TERMS & CONDITIONS

- 1) Prices should be 'DDP' delivery duty paid at DEWA stores.
- 2) Quotation to be submitted only in local currency U.A.E Dirhams
- 3) DEWA Standard payment terms is '30 days credit' from the date of acceptance of material
- 4) No DEWA staff or his or her relatives up to third degree should have ownership or partnership in your company, and your participation in DEWA tenders / RFQs should not constitute a Conflict or perceived Conflict of Interest.
- 5) The offered product and/ or services in the Quotation, shall be conforming and in accordance with DEWA Energy Management Policy & EnMS Manual.





RFQ NUMBER : 2012201698

DATE : 30.03.2022

REQ No : 1012201420

REQ TITLE : BATTERY 1012201420

DELIVERY LOCATION : 0051 - CENTR STROE(TRN)

CLOSING DATE : 07.04.2022

CLOSING TIME : 10:00:00

SUPPLIER'S REMARKS:

SUPPLIER'S SIGNATURE AND STAMP